

## Advanced Biocide Activator

- Highest Level of Concentrated Biocide
- Performance Enhancer for Sea Hawk Solvent based Antifoulants



## ZPT-Based Antifoulant Additive



OVER  
35  
YEARS

## PRODUCT DESCRIPTION

If you desire the ultimate in antifoulant performance, then add Bio-Boost Activator to every gallon. Bio-Boost is an antifoulant paint additive loaded with the newest biocide technology available. Its' high strength will add extra protection against the harshest marine environments.



## PRODUCT INFORMATION

**Size:** 1/2 Pint

**Colors:** N/A

**Finish/Sheen:** N/A

**Zinc Omadine:** 31.11%

**Volume Solids:** 23% (±2%)

**Solids by Weight:**

**Mix Ratio:** 1/2 to 1 Pint per Gallon

**Shipping Weight:** 2.1 lbs./qt.

**Flash Point:** 100°F

**VOC:** 565 Grams/Liter or 4.7 lbs/gal

## SAFETY

Prior to use, obtain and consult the "Material Safety Data Sheet" of this product for health and safety information. Read and observe all precautionary notices on container labels.

## BENEFITS VS. COMPETITION

- The Only Advanced Biocide Additive on the Market
- Boost to the Highest Level of Antifoulant Protection
- Designed ONLY for these specific Sea Hawk Antifoulants:  
AF-33, Biocop TF, Cukote, Cukote Biocide, Islands 77, Mission Bay, Sharkskin, Smart Solution, Talon, Tropikote, and Tropikote Biocide

## Mixing Instructions

Stir or shake Bio-Boost thoroughly before adding to antifoulant. Mix 1 Bio-Boost to one gallon of Sea Hawk antifoulant mixing or shaking for at least 5 minutes. Apply antifoulant with two hours of addition.



**Bio-Boost™**  
**Item #2300**  
Technical Data Sheet

**May only be added to:** AF-33 3300 Series  
Biocop TF 1201-1 Series  
Cukote 3400 Series  
Cukote Biocide 3500 Series  
Islands 77 Plus 7700 Series  
Mission Bay 4000 Series  
Sharkskin 6100 Series  
Smart Solution 4700 Series  
Talon 6000 Series  
Tropikote 2100 Series  
Tropikote Biocide 2200 Series

**Induction Time:** Not Applicable

**Pot Life:** Not Applicable

**Note: Adding Bio-Boost to any other antifouling other than listed above may cause instability and result in unusable product. Antifoulant must be applied within 2 hours of addition.**

**Precautionary Statements**

Be sure to wear protective gloves and goggles when handling Bio-Boost. May cause eye irritation and harmful if absorbed through the skin. Consult your Sea Hawk Representative for more information.