

# 1. Product and Company Identification

Material name Bottom Protect Epoxy Primer Activator Component

Version # 01

Revision date 10-11-2019 Product code 8000B

Product use Marine Epoxy Primer Activator

Manufacturer/Supplier Blue Water Marine Paint (New Nautical Coatings, Inc.)

14805 49<sup>th</sup> Street North Clearwater, FL 33762 USA Only:-800-347-4464 International: 727-523-8053

**Emergency** CHEMTREC day or night inside USA & Canada

1-800-424-9300

CHEMTREC day or night inside outside USA & Canada

1-703-741-5970

#### 2. Hazards Identification

#### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
Muta. 1B H340
Carc. 1A H350
STOT RE 1 H372
Asp. Tox. 1 H304
Aquatic Chronic 3 H412

### 2.2. Label elements

### **GHS-US labelling**

Hazard pictograms (GHS-US)





GHS05

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H340 - May cause genetic defects

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust, fume, mist, spray, vapors

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors

P264 - Wash hands, forearms and face thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves, protective clothing

P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center

P302+P352 - If on skin: Wash with plenty of soap and water

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing P308+P313 - If exposed or concerned: Get medical advice/attention

P310 - Immediately call a doctor, a poison center P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse

P362+P364 - Take off contaminated clothing and wash it before reuse

P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

# 3. Composition / Information on Ingredients

Components	CAS#	Percent	
Polyamide Resin	Proprietary	< 38.0%	
2-Butoxyethanol	111-76-2	<7.0%	
High Flash Naphtha	64742-94-5	>4.0%	
Xylene	1330-20-7	>12.0%	
Magnesium Silicate	14807-96-6	< 40.0%	

### 4. First Aid Measures

Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention. In case of irritation from airborne exposure, move to fresh air. Get medical attention if symptoms persist.	
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation persists. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.	
Inhalation	Move person to fresh air. If person is not breathing, call911 or an ambulance then give artificial respiration. Call a poison control center or doctor immediately for further treatment advice For additional information in case of emergency call toll free CHEMTREC 1-800-424-9300. Have product container or label with you when calling a poison control center or doctor for treatment.	
Ingestion	DO NOT INDUCE VOMITING UNLESS TO DO SO BY MEDICAL PERSONEL. Call a poison control center or doctor immediately for treatment advice. NEVER give anything by mouth to an unconscious person.	

### 5. Fire Fighting Measures

**Flammable properties** Flammable, Category 3, Flash Point 77-83 °F.

**Extinguishing media** - Water, water fog, foam, dry chemical, carbon dioxide

Firefighting equipment/instructions. - Self-contained breathing apparatus and full protective clothing

Hazardous combustion products - Carbon and Nitrogen oxides.

### 6. Accidental Release Measures

Personal precautions Ensure adequate ventilation. Wear suitable protective clothing. See Section 8 of the SDS for

Personal Protective Equipment.

**Environmental precautions** Collect using non-sparking equipment and dispose of spillage in accordance with state and local

regulations.

**Methods for containment** Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements

or confined areas.

Methods for cleaning up Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Use a non-combustible

material like vermiculite, sand or earth to soak up the product and place into a container for later

disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece).

Never return spills to original containers for re-use. Following product recovery, flush area with

water. Clean surface thoroughly to remove residual contamination.

Other information Clean up in accordance with all applicable regulations.

# 7. Handling and Storage

Handling Avoid breathing mists or vapors. Avoid contact with eyes, skin, and clothing. Use only with

adequate ventilation. Wash thoroughly after handling. Observe good industrial hygiene practices.

Storage Keep container tightly closed and in a well-ventilated place. Store in closed original

container at room temperature. Store away from incompatible materials.

## 8. Exposure Controls / Personal Protection

Components	Value
Polyamide Resin (Proprietary)	
STEL	Not Available
TWA	Not Available
IVVA	Not Available
Magnesium Silicate (14807-96-6)	
STEL	Not Available
TWA	10 mg/M3
	io mg/mo
2-butoxyethanol (111-76-2)	
STEL	N/Av
TWA	20 ppm
	20 pp
Xylene (1330-20-7)	
STEL	100 ppm
TWA	100 ppm

## US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Polyamide Resin	PEL	Not Available	

High Flash Naphtha PEL 25 ppm

Magnesium Silicate PEL 10 mg/M3

2-Butoxyethanol PEL 50 ppm

Xylene PEL 50 ppm

Ensure adequate ventilation, especially in confined areas. Must control air contamination to their

exposure limits.

### Personal protective equipment

**Eye / face protection** Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

**Skin protection** Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure.

Contact glove manufacturer for specific information.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or

canister.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

# 9. Physical & Chemical Properties

Appearance Liquid.

Color Amber

Odor Pleasant.

Odor threshold Not available.

Physical state Liquid. Form Liquid.

pH Not ApplicableMelting point Not Applicable.Freezing point Not Applicable.

**Boiling point** 244 °F **Flash point** 77-83 ° F.

**Evaporation rate** Faster than water.

Flammability limits in air, lower, 1.10
Specific gravity 1.34

Solubility (water) Not Soluble.

Partition coefficient (n-octanol/water) No data available.

Vapor Pressure Unknown

Vapor DensityHeavier than airAuto-ignition temperatureNot available.Decomposition temperatureNot available.

### 10. Chemical Stability & Reactivity Information

Chemical stability Material is stable under normal conditions.

Conditions to avoid Contact with flames and high heat.

Incompatible materials Strong acids and alkalis.

Hazardous decomposition products - Carbon and Nitrogen Oxides

Possibility of hazardous reactions - Hazardous decomposition will not occur

# 11. Toxicological Information

## Toxicological data

Components	Test	Results
Polyamine Resin	Acute Data	Not Available
High Flash Naphtha	Acute Dermal	LD50 >3100 mg/Kg
	Acute Oral	LD50 >2900 mg/Kg
Magnesium Silicate	Acute Oral	LD50 10000 mg/Kg
2-Butoxyethanol	Acute Dermal (Rabbit)	LD50 400 – 500 mg/Kg
	Acute Oral (rat)	LD50 > 530 mg/Kg
Xylene	Acute Oral	LD50 5000mg/Kg
	Acute Dermal	LD50 1240 mg/Kg

## **Acute effects**

Routes of Exposure - Eye contact, skin contact, inhalation and ingestion

Eye Contact - eye irritation

Skin Contact - skin irritation

Inhalation - irritating to respiratory system

Ingestion - irritating to digestive tract

Chronic effects - Unknown

Carcinogenicity - This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

# 12. Ecological Information

Ecotoxicological data

Components Test Results

No ingredients expected to be harmful to aquatic life Product does not contain any pesticides

**Ecotoxicity -** Not expected to be harmful to aquatic organisms.

Persistence and degradability - Unknown

Bioaccumulation / Accumulation - Unknown

Partition coefficient (n-octanol/water) - Unknown

## 13. Disposal Considerations

**Disposal instructions**Dispose of contents/container in accordance with local/regional/national/international regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings and disposal

procedures.

# 14. Transport Information

**UN Number - UN1263** 

**UN Proper Shipping Name - PAINT** 

Transport Hazard Classes \

DOT (Domestic Surface Transportation - Proper Shipping Name - PAINT

DOT Hazard Class - 3 UN/NA Number - UN1263 UN Packing Group - III

IMO/IMDG (Ocean Transportation)

**IMDG Shipping Name - PAINT** 

IMDG Hazard Class - 3, Sub Class - 3

IMDG Packing Group - III, System Reference Code - 1

**Environmental Hazards** 

**IMDG - Marine Pollutant - No** 

Special Precautions for User - Not Regulated

Transport in bulk according to Annex II of MARPOL 7378 and the IBC Code

Not Applicable

## 15. Regulatory Information

**US federal regulations** This product is hazardous according to OSHA 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

US TSCA Section 12(b) Export Notification: For exportation, please follow directions provided by the

Federal EPA on Export of Registered Pesticides.

Drug Enforcement Administration (DEA) (21 CFR 1308.11-15) - Not controlled

State regulations This product contains a chemical or chemicals known to the State of California to cause cancer,

birth defects or other reproductive harm.

#### 16. Other Information

HMIS® ratings Health: 3

Flammability3 Physical hazard: 2

NFPA ratings Health: 3

Flammability: 3 Instability: 0

**Disclaimer** The information contained herein is based on data considered accurate. However, no warranty is

expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Blue Water Marine assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Blue Water Marine assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety

procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

**Issue date** 10-11-2019