



# PETTIT PAINT

## MATERIAL SAFETY DATA SHEET

<b>Supplier:</b>	Kop-Coat, Inc. Marine Group 36 Pine Street Rockaway, NJ 07866	<b>EMERGENCIES:</b> Health/spills.....: Chemtrec Assistance.....: Chemtrec Outside USA.....:	800-548-0489 800-424-9300 703-527-3887
		<b>Kop-Coat, Inc.</b> Product Information.....: Outside USA.....:	800-221-4466 973-625-3100

### 1. Product Information

<b>Product name</b>	1863 Alumaspray + Aerosol Antifouling Paint Black
<b>Product code</b>	1186300\1

**Issuing date:** 06/29/2010

**Contact person:**

Environmental Health & Safety Mgr

### 2. Hazards identification

#### Emergency Overview

**Appearance:** Black aerosol

**Odor:**

Solvent

**Hazards:** DANGER!

Contents under pressure. Extremely flammable liquid and vapor.  
Vapors may cause flash fire. Harmful if swallowed. Causes skin burns and eye irritation. Vapor harmful.

#### Potential health effects

#### **Primary Routes of Entry:**

Eye contact, ingestion, skin contact, inhalation, and absorption.

#### **Eye contact:**

May cause eye irritation. Symptoms may include stinging, tearing, and redness of eyes.

#### **Ingestion:**

Aspiration of this product into the lungs during ingestion, gagging or vomiting may cause lung damage, which can be fatal. May cause gastrointestinal distress. Symptoms may include irritation to the mouth, throat and stomach and gastrointestinal disturbances such as nausea, vomiting or diarrhea.

#### **Skin contact:**

May cause severe skin irritation and/or skin damage depending upon extent of exposure; signs and symptoms may include blistering, burns and/or possible scarring. May be harmful if absorbed through the skin in toxic amounts and

cause systemic effects. Prolonged and/or repeated skin contact may cause symptoms including dryness, itching, burning sensation, cracking and redness.

**Inhalation:**

May cause irritation to the nose, throat and respiratory tract. Inhalation of high concentrations of vapors may cause respiratory tract irritation and central nervous system depression. Symptoms may include headache, nausea, dizziness and drowsiness. Continued inhalation may result in unconsciousness or death. Serious risk of suffocation when in confined area.

**Chronic effects:**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged or repeated dermal exposure to this product can cause skin dermatitis characterized by red, dry, scaly skin.

**Target Organs:**

Not Determined

This product contains carcinogens or potential carcinogens as listed by IARC or NTP. See Section 3 NTP, IARC (Carc.) columns for chemical identification.

### 3. Composition/information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Weight %</u>	<u>Carc</u>
Toluene	108-88-3	30 - 50	
Propane	74-98-6	20 - 30	
Zinc Oxide	1314-13-2	10 - 20	
Petroleum distillates, hydrotreated light	64742-47-8	1 - 10	
Barium Sulfate	7727-43-7	1 - 10	
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1 - 10	
Zinc pyrithione	13463-41-7	1 - 10	
Carbon Black	1333-86-4	< 1	*
Naphthalene	91-20-3	< 1	*

### 4. FIRST AID MEASURES

**Eye contact:**

Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into unaffected eye or onto the face. Call poison control center, hospital emergency room, or physician immediately.

**Ingestion:**

NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 2 to 8 oz. (60 to 240 mL) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Immediately obtain medical advice.

**Skin contact:**

As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately wash with lukewarm, gently flowing water and non-abrasive soap for 15-20 minutes. Immediately obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

**Inhalation:**

This product is flammable. Take proper precautions (e.g. remove any sources of ignition). Remove source of contamination or move victim to fresh air. Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Call poison control center, hospital emergency room, or physician immediately.

**Note to Physician :**

There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

## 5. FIRE-FIGHTING MEASURES

**Flash point** < 0 deg F

**Extinguishing media:**

Use alcohol foam, dry chemical, carbon dioxide or any Class B fire extinguishing agent. Water may be unsuitable for extinguishing fires. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Hazardous combustion products:**

Combustion may produce carbon monoxide, carbon dioxide, and irritating or toxic vapors and gases.

**Protective equipment and precautions for firefighters:**

Extremely flammable liquid and vapor! Evacuate area and fight fire from a safe distance. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal & Environmental Precautions:**

Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal using non-sparking tools.

**Methods of Containment & Clean-up and Other Information:**

This product, if released in large enough quantities, may need to be reported to the US Coast Guard National Response Center at 1-800-424-8802. Contain spills with dikes and absorbents (sand, earth, dry chemical absorbent) to prevent migration and entry into waterways.

## 7. HANDLING AND STORAGE

**Handling:**

Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not store above 120°F, or in direct sunlight. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Keep container closed and upright when not in use. To prevent generation of static discharges, use bonding/grounding connection when transferring material. Vapors may accumulate and travel to distant ignition sources and flashback. Extinguish all sources of ignition including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Since empty containers may retain product residue and flammable vapors, observe precautions even after container is emptied. Do not cut, puncture, or weld on or near empty containers. Do not smoke where product is used or stored. Avoid contact with eyes, skin or clothing. Avoid inhalation (vapor, mist, dust or fume, as applicable). Use only with adequate ventilation. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling.

**Storage:**

Keep containers closed when not in use. Store in cool, well ventilated space away from incompatible materials. Store in areas/buildings designed to comply with OSHA 1910.106. Store away from sources of ignition and heat.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Z-1 PEL</u>	<u>Z-2 PEL</u>	<u>ACGIH TLV</u>
Toluene	108-88-3		200 PPM	50 PPM
Propane	74-98-6	1800 MGM3 (1000 PPM)		
Zinc Oxide	1314-13-2	15 MGM3		2 MGM3
Petroleum distillates, hydrotreated light	64742-47-8			
Barium Sulfate	7727-43-7	5 MGM3		10 MGM3
Solvent naphtha (petroleum), heavy aromatic	64742-94-5			
Zinc pyrrhione	13463-41-7			
Carbon Black	1333-86-4	3.5 MGM3		3.5 MGM3
Naphthalene	91-20-3	50 MGM3 (10 PPM)		10 PPM

**Engineering measures:**

Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits. Supplementary local exhaust ventilation may be necessary in poorly ventilated spaces, during spraying, heating or other non-routine activities.

**Eyeface protection:**

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.

**Skin protection:**

Chemical-resistant, flexible-type gloves (neoprene, nitrile or equal) to prevent contact. Gloves should be rinsed and removed immediately after use. Wash hands after removing gloves. Applicators and other handlers working with the concentrate must wear coveralls over long-sleeved shirt and long pants, chemical-resistant apron, footwear and socks.

**Respiratory protection:**

Respiratory protection may be necessary under certain use conditions. Under such conditions, an appropriate, properly fitted NIOSH-approved respirator must be worn. If respirators are used, a program should be instituted to assure compliance with 29 CFR 1910.34 and 42 CFR 84.

**General hygiene considerations:**

Facilities utilizing this material should be equipped with an eyewash station and safety shower. Thoroughly clean shoes and wash contaminated clothes before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Aerosol
<b>Appearance:</b>	Black aerosol
<b>Odor</b>	Solvent
<b>pH</b>	Not applicable.
<b>Boiling point</b>	not determined
<b>Flash point</b>	< 0 deg F
<b>Solubility in water:</b>	Not applicable.
<b>Specific Gravity:</b>	0.86
<b>Weight per gallon (LB/GAL) :</b>	7.16
<b>Evaporation rate (n-Butyl acetate = 1):</b>	< 1
<b>Volatile by Weight (including water and exempt compounds) (%):</b>	74.70
<b>Volatile Organic Content (VOC):</b>	5.35 lb/gal

## 10. STABILITY AND REACTIVITY

**Stability:**

Stable under normal conditions.

**Incompatibility:**

Oxidizing agents, acids and bases. Keep away from heat, sparks and open flames.

**Hazardous decomposition products:**

Carbon monoxide, carbon dioxide, oxides of nitrogen and other toxic organic compounds.

## 11. TOXICOLOGICAL INFORMATION

Naphthalene: Laboratory animals exposed to high levels of naphthlene showed evidence of red blood cell destruction with anemia, fever, jaundice, and kidney and liver damage. Naphthalene caused an increased incidence of tumors in the nose in rats.

Zinc pyrrhione (CAS# 13463-41-7): Animal studies have found skeletal muscle atrophy and peripheral nerve damage characterized by general muscle weakness. These effects have not been observed in primates, which suggests the effects would not occur in humans. Zinc pyrrhione (CAS# 13463-41-7): Animal studies have found skeletal muscle atrophy and peripheral nerve damage characterized by general muscle weakness. These effects have not been observed in primates, which suggests the effects would not occur in humans.

Toluene (CAS# 108-88-3): Prolonged intentional toluene abuse and overexposure to laboratory animals has been associated with central and peripheral nervous system, liver, kidney, blood, vision, hearing and heart damage. Overexposure to animals has been associated with adverse reproductive and developmental effects.

## 12. ECOLOGICAL INFORMATION

Contact Kop-Coat for ecological data on individual components of this material.

## 13. DISPOSAL CONSIDERATIONS

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

**Transportation:**

This product can be reclassified as Consumer Commodity, ORM-D, when shipped by ground.

**By Ground:****DOT Hazard Class:**

See above.

**DOT Proper Shipping Name:****DOT Packing Group:****DOT UN Number:****By Air:**

IATA Hazard Class: not determined

IATA Proper Shipping Name:

IATA Packing Group:

IATA UN Number:

By Sea:

IMDG Hazard Class: not determined

IMDG Proper Shipping Name:

IMDG Packing Group:

IMDG UN Number:

15. REGULATORY INFORMATION

EPA registration number: 60061-120

Pest Registration Act number: Not applicable.

Other:

Not applicable.

Chemical Name	CAS-No.	TSCA 12B	SARA 313	TSCA	DSL	EINECS	Prop 65	Whmis
Toluene	108-88-3		*	*	*	*	*	*
Propane	74-98-6			*	*	*		
Zinc Oxide	1314-13-2		*	*	*	*		
Petroleum distillates, hydrotreated light	64742-47-8			*	*			
Barium Sulfate	7727-43-7			*	*	*		
Solvent naphtha (petroleum), heavy aromatic	64742-94-5			*	*	*		*
Zinc pyrithione	13463-41-7		*	*	*			
Naphthalene	91-20-3	*	*	*	*	*	*	*

16. OTHER INFORMATION

HMIS Health: 2\*      HMIS Flammability: 4      HMIS Physical Hazard: 0

NFPA Health: 2      NFPA Flammability: 4      NFPA Instability/Reactivity: 0

NOTICE: This document is generated for the purpose of distributing health, safety, and environmental data. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed, or implied, regarding correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. Kop-Coat makes no warranty with respect thereto and disclaims all liability from reliance thereon.

Key:

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service Registry Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CERCLA RQ	CERCLA Reportable Quantity
CFR	Code of Federal Regulations
CPR	Cardiopulmonary resuscitation
DSL	Domestic Substances List of Canada
EINECS	European Inventory of Existing Chemical Substances
EPCRA	Emergency Planning and Community Right-to-know Act

<b>EPCRA EHS</b>	<b>EPCRA Extremely Hazardous Substance</b>
<b>EPCRA TPQ</b>	<b>EPCRA Threshold Planning Quantity</b>
<b>oF</b>	<b>Fahrenheit degrees</b>
<b>g/l</b>	<b>Grams per liter</b>
<b>gal</b>	<b>Gallons</b>
<b>Group A3</b>	<b>Carcinogen Category - Confirmed Animal Carcinogen with Unknown Relevance to Humans</b>
<b>Group A4</b>	<b>Carcinogen Category - Not Classifiable as a Human Carcinogen</b>
<b>HMIS</b>	<b>Hazardous Materials Identification System - Chemical Rating</b>
<b>IARC</b>	<b>International Agency for Research on Cancer</b>
<b>lbs or LBS</b>	<b>Pounds</b>
<b>MGM3</b>	<b>Milligrams per cubic meter</b>
<b>MIR</b>	<b>Maximum Incremental Reactivity</b>
<b>MSDS</b>	<b>Material Safety Data Sheet</b>
<b>NFPA</b>	<b>National Fire Protection Association</b>
<b>NIOSH</b>	<b>National Institute for Occupational Safety and Health</b>
<b>NTP</b>	<b>National Toxicology Program</b>
<b>OSHA</b>	<b>Occupational Safety and Health Administration</b>
<b>PEL</b>	<b>Permissible Exposure Limit</b>
<b>PPM</b>	<b>Parts per million</b>
<b>Proposition 65</b>	<b>California's Safe Drinking Water and Toxic Enforcement Act</b>
<b>SARA</b>	<b>Superfund Amendments and Reauthorization Act</b>
<b>TLV</b>	<b>Threshold Limit Value</b>
<b>TSCA</b>	<b>Toxic Substances Control Act</b>
<b>USEPA</b>	<b>United States Environmental Protection Agency</b>
<b>VOC</b>	<b>Volatile Organic Compound</b>
<b>VOL</b>	<b>Volume</b>
<b>WT</b>	<b>Weight</b>
<b>WHMIS</b>	<b>Canadian Workplace Hazardous Materials Information System</b>
<b>UN</b>	<b>United Nations</b>

ANSI KC 1.74