



Material Data Safety Sheet

Emergency Telephone Numbers: 800-528-0997; 813-523-8053

REVIEW/UPDATE: 02/15/2005 BY: *Mario Garneau*

SECTION ONE - PRODUCT DESCRIPTION

NAME: SEA HAWK 1255 Black Barrier Part A
 CHEMICAL DESCRIPTION: Coal Tar Epoxy
 FORMULA: Solution Epoxy Formulation

SECTION TWO - HAZARDOUS INGREDIENTS

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ#	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
XYLENE	<20%	1130-20-7	100PPM	N/A	N	N	N	N	N	N	(1)
TAR PITCH	>75%	65996-89-6	100ppm	NE	N	Y	Y	N	N	N	(1)
MIBK	10%	13463-67-7	10MG	N/A	N	N	N	N	N	N	(1)
EP	5%	14807-96-6	2MG	N/A	N	N	N	N	N	N	(1)
HF NAPHTHA	5%	NA	NE	N/A	N	N	N	N	N	N	(1)

SECTION THREE - PHYSICAL DATA

APPEARANCE and Odor: Liquid Solvent
 VAPOR PRESSURE: .2 PSIG @ 100° F
 SPECIFIC GRAVITY (Water .1) : .94
 SOLUBILITY IN WATER: None

BOILING POINT: >241-308° F
 VAPOR DENSITY (Air = 1); 3.7
 VOTILE BY WEIGHT: 20%
 EVAPORATION RATE: (Water = 1) <1

SECTION FOUR - FIRE AND EXPLOSION DATA

FLASH POINT (°F / °C) [CLOSED CUP] : 31° C
 FLAMMABLE LIMIT: -LEL 1.0
 -UEL 7.0

EXTINGUISHER MEDIA: Carbon Dioxide Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighter must wear self contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water vapor.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION FIVE - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section Two

EFFECTS OF OVEREXPOSURE

Inhalation: May be harmful or fatal if inhaled. May cause lung injury. Causes nose and throat irritation. Vapor may affect the brain or nervous system causing dizziness, headaches, or nausea.
 Skin Contact: Causes skin burns. May be harmful if absorbed through the skin.
 Eye Contact: Causes eye burns. Do not get in eyes.

EMERGENCY & FIRST AID PROCEDURES:

Inhalation: Move subject to fresh air.
 Eye/skin Contact: Flush eyes with large amounts of water for at least 15 minutes . see physician if irritation persists.. Wash affected skin area with soap and water.



PREMIUM YACHT FINISHES

14805 49th Street North • Clearwater, FL 33762
1-800-528-0997 U.S.A. only • (727) 523-8053 International

1255 A

Black Barrier

Coal Tar Epoxy Primer

=====

SECTION SIX - PHYSICAL HAZARDS (REACTIVITY DATA)

=====

STABILITY: STABLE: YES
 UNSTABLE: NO

CONDITIONS TO AVOID IF UNSTABLE: N/A

INCOMPATIBILITY WITH OTHER MATERIALS: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID UNCONTROLLED POLYMERIZATION: NA

=====

=====

SECTION SEVEN - STORAGE, HANDLING, SPILL AND DISPOSAL PROCEDURES

=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below 38° C/100°f, Keep from freezing. Use with adequate ventilation. Use respirator if engineering controls are not adequate to maintain mist, vapor or dust below applicable standards.

STEPS TO FOLLOW IF MATERIAL IS SPILLED OR RELEASED: Comply with all applicable health and environmental regulations. Ventilate area. Evacuate all unnecessary personnel. Use absorbent to pick up residue, place in proper container and dispose of properly.

WASTE DISPOSAL METHODS: Dispose of in accordance with all applicable regulations. Avoid discharge into natural waters.

=====

=====

SECTION EIGHT - PERSONAL PROTECTION INFORMATION

=====

RESPIRATORY PROTECTION: Wear Respirator (MSHA/NIOSH) suitable for concentration and types of contaminants.

VENTILATION: Local [X] Other
 Mechanical [X]

PROTECTIVE GLOVES: Impervious . Rubber, Neoprene.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1)

OTHER PROTECTIVE EQUIPMENT: NONE

=====

=====

SECTION NINE - SPECIAL PRECAUTIONS None

=====

OTHER PRECAUTIONS: Keep away from children, pets, livestock, and foodstuffs

=====

=====

SECTION TEN - OTHER REGULATORY INFORMATION

=====

CALIFORNIA PROPOSITION 65 CHEMICALS: NONE

TSCA CERTIFICATION: All Chemicals in this product are listed, or exempt from listing, on the TSCA Inventory.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution.

Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third parties caused by this material. User assumes all risks associated with the use of this material.

(1) Abbreviations: N/E . Not Established, Supp. Conf. . Supplier Confidential, N/A . Not Applicable, ppm . Parts Per Million, mg/m³ . Milligrams per cubic meter, N- NO, Y . YES.



Material Data Safety Sheet

Emergency Telephone Numbers: 800-528-0997; 813-523-8053

REVIEW/UPDATE: 02/15/2005 BY: *Mario Garneau*

SECTION ONE - PRODUCT DESCRIPTION

NAME: SEA HAWK 1255 Black Barrier Part B
 CHEMICAL DESCRIPTION: Coal Tar Epoxy
 FORMULA: Diglycidyl Ether Resin

SECTION TWO - HAZARDOUS INGREDIENTS

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ#	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
EPOXY RESIN	100%	25068-38-6	N/A	N/A	N	N	N	N	N	N	(1)

SECTION THREE - PHYSICAL DATA

APPEARANCE and Odor: Liquid Solvent
 VAPOR PRESSURE: 1MM HG @ at 77° F
 SPECIFIC GRAVITY (Water .1) : .94
 SOLUBILITY IN WATER: None

BOILING POINT: >200° F
 VAPOR DENSITY (Air = 1); Heavier, than air
 VOTILE BY WEIGHT: nil
 EVAPORATION RATE: (Water = 1) nil

SECTION FOUR - FIRE AND EXPLOSION DATA

FLASH POINT (°F / °C) [CLOSED CUP] : 490° F
 FLAMMABLE LIMIT: -LEL n/a
 -UEL n/a

EXTINGUISHER MEDIA: Carbon Dioxide Water Fog
 SPECIAL FIRE FIGHTING PROCEDURES: Fire fighter must wear self contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water vapor.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION FIVE - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section Two

EFFECTS OF OVEREXPOSURE

Inhalation: May be harmful or fatal if inhaled. May cause lung injury. Causes nose and throat irritation. Vapor may affect the brain or nervous system causing dizziness, headaches, or nausea.

Skin Contact: Causes skin burns. May be harmful if absorbed through the skin.

Eye Contact: Causes eye burns. Do not get in eyes.

EMERGENCY & FIRST AID PROCEDURES:

Inhalation: Move subject to fresh air.

Eye/skin Contact: Flush eyes with large amounts of water for at least 15 minutes . see physician if irritation persists.. Wash affected skin area with soap and water.

SECTION SIX - PHYSICAL HAZARDS (REACTIVITY DATA)

STABILITY: STABLE: YES
UNSTABLE: NO

CONDITIONS TO AVOID IF UNSTABLE: N/A

INCOMPATIBILITY WITH OTHER MATERIALS: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID UNCONTROLLED POLYMERIZATION: NA

SECTION SEVEN - STORAGE, HANDLING, SPILL AND DISPOSAL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below 38° C/100°f, Keep from freezing. Use with adequate ventilation. Use respirator if engineering controls are not adequate to maintain mist, vapor or dust below applicable standards.

STEPS TO FOLLOW IF MATERIAL IS SPILLED OR RELEASED: Comply with all applicable health and environmental regulations. Ventilate area. Evacuate all unnecessary personnel. Use absorbent to pick up residue, place in proper container and dispose of properly.

WASTE DISPOSAL METHODS: Dispose of in accordance with all applicable regulations. Avoid discharge into natural waters.

SECTION EIGHT - PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear Respirator (MSHA/NIOSH) suitable for concentration and types of contaminants.

VENTILATION: Local ☒ Other ☐
Mechanical ☐ ☒

PROTECTIVE GLOVES: Impervious . Rubber, Neoprene.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1)

OTHER PROTECTIVE EQUIPMENT: NONE

SECTION NINE - SPECIAL PRECAUTIONS None

OTHER PRECAUTIONS: Keep away from children, pets, livestock, and foodstuffs

SECTION TEN - OTHER REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65 CHEMICALS: NONE

TSCA CERTIFICATION: All Chemicals in this product are listed, or exempt from listing, on the TSCA Inventory.

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using the material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution.

Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third parties caused by this material. User assumes all risks associated with the use of this material.

(1) Abbreviations: N/E . Not Established, Supp. Conf. . Supplier Confidential, N/A . Not Applicable, ppm . Parts Per Million, mg/m³ . Milligrams per cubic meter, N- NO, Y . YES.